VERSALIFT UNDERSTALIFT UNDERSTA







Available for class B driving licence



Belt driven hydraulic pump



No outriggers for quick setup & packing





1 kV certified low voltage insulation



EJ-086-WJ

«VERSALIFT» LT-110-TB

Available specifications















Length: 6,140 mm

Height: 2,730 mm

Wheelbase: 3,220 mm

Key features



1 man "Eco" fibreglass bucket



Rear platform (Bucket center stowed)



Lower control panel (wired remote control panel)



RLC (Relay Lefthand proportional Controls): Fixed outreach and 1 action at a time

Distributor

Notes

Technical information is subject to change without prior notice. Images may show optional equipment. Installations and/or options may not be available in your specific region.

- * Depending on the vehicle.
- ** Max payload with a driver, a passenger and a full tank of fuel (220 kg added to the installation weight).

C714R (Versalift LT-30-110-TB on Ford Ranger Pickup) - revision 2018/10 www.TimeIntl.dk



Additional equipment 12V Electric emergency pump Flashing light under the bucket Power outlets in the bucket Amber LED beacons on the turret Parallelogram door switch Tilt sensor Plastic toolbox for the bucket Removable LED spotlight for the bucket Sliding work table for the bucket Flashing lights on the vehicle

3/5°

1 kV

Diagramme(s)

