

# VOE36IVIHi

## **INSULATED PLATFORM**





CAT C 46kV INSULATED



MATERIAL HANDLING CAPABILITY



OVER CENTRE MODELS



TWIN 130KG SWL BUCKETS



360° CONTINUOUS ROTATION



TYPE APPROVED



## SPECIFICATIONS


Working height*	13.3m
Platform height	11.3m
Max. outreach	9.3m
Max. outreach with material handling	7.3m
Max. bucket capacity (SWL)	2x130kg
Max. material handling (MH)	670kg
Min. GVW	12500kg
Bucket rotation	180°
Insulation rating to ANSI	A92.2 CAT C 46kV

Specifications are subject to vehicle and options fitted - please contact us for further information \* Subject to mounting vehicle

## STANDARD

- A-frame outriggers to rear, radial outriggers to front
- 2 x 130kg single operative buckets
- Jib and winch with 670kg materials handling lifting capability
- Jib pole with 120° arc
- Over centre boom geometry
- Lower boom insert
- 360° continuous rotation
- Full pressure hydraulic controls to bucket and pedestal
- Hydraulic tool outlet at operator's bucket
- Emergency stop at platform and pedestal
- Full functions at ground
- Full platform functionality on emergency power
- 4 x outrigger speader pads with carrying frames
- Protective covers for insulated boom parts
- Tree guards for bucket protection

#### VOE36MHi **METRES**



Working envelope at 2x130kg bucket SWL

/ersalifi


I Altendiez Way, Latimer Park, Burton Latimer, Kettering. NNI5 5YT T: 01536 721010 F: 01536 721111 E: sales@versalift.co.uk W: www.versalift.co.uk TRACK MOUNTED

## OPTIONS

- H-frame outriggers to front
- Earth grounding cable
- Bespoke aluminium toolboxes
- Bespoke fibreglass GRP lockers
- Thermostatically controlled locker heaters
- Chapter 8 compliance

As our insulated platforms can be configured and specified to customer requirements, please contact Versalift direct to discuss your particular situation and operation conditions

### **Material Handler Capacity**





Efficient operation of materials handler with twin bucket system

INSULATED PLATFORI

**VOE36MH** 

Jib and winch provides up to 670kg lifting capability



Can work on live network up to 46kV CAT C



Improved stability with proven A-frame and radial outrigger system



Mounted on a Mercedes Unimog U423 Euro 6

The photographs in this brochure are for promotional purposes only. Specifications are subject to change without notice.













PICK-UP MOUNTED

VAN MOUNTED CHASSIS MOUNT TRUCK MOUNTED

INSULATED PLATFORM