

VO-350/355/360-MHI/XMHI

Insulated Articulated Overcenter /Telescopic Aerial Device

- **WORKING HEIGHT:** Up to 65 ft 4 in (19.9 m)
- **HORIZONTAL REACH:** Up to 52 ft 2 in (15.9 m)
- **PLATFORM CAPACITY:** Up to 800 lbs (360 kg)
- **JIB CAPACITY:** Up to 2000 lbs (900 kg)

OPTIONAL
**PILOT
CONTROL
SYSTEM**

TruGuard®
STANDARD



VO-355-XMHI model shown here.

VERSALIFT®



VO-350/355/360-MHI/XMHI

Insulated Articulated Overcenter /Telescopic Aerial Device



VO-350-MHI

VO-355-MHI

VO-360-MHI

GENERAL SPECIFICATIONS:

(Based on 40 in Frame)

Horizontal Reach Overcenter	42 ft 2 in (12.9 m)	47 ft 2 in (14.4 m)	52 ft 2 in (15.9 m)
Horizontal Reach Non-Overcenter	31 ft 11 in (9.7 m)	34 ft 11 in (10.6 m)	37 ft 11 in (11.6 m)
Horizontal Reach Non-Overcenter with X	39 ft 2 in (11.9 m)	43 ft 2 in (13.2 m)	47 ft 1 in (14.4 m)
Platform Capacity Single 1-Man	450 lbs (205 kg)	450 lbs (205 kg)	450 lbs (205 kg)
Platform Capacity Single 2-Man	800 lbs (360 kg)	800 lbs (360 kg)	600 lbs (270 kg)
Total Platform Capacity Dual 1-Man	800 lbs (360 kg)	800 lbs (360 kg)	Not available
Total Platform Capacity Dual 1-Man With Dual Controls	800 lbs (360 kg)	700 lbs (320 kg)	Not available
Rotation	360° Continuous	360° Continuous	360° Continuous
Platform Rotation	90°	90°	90°
Height to Bottom of Platform	50 ft 4 in (15.3 m)	55 ft 4 in (16.9 m)	60 ft 4 in (18.4 m)
Working Height	55 ft 4 in (16.9 m)	60 ft 4 in (18.4 m)	65 ft 4 in (19.9 m)
Stowed Travel Height	11 ft 0 in (3.4 m)	11 ft 0 in (3.4 m)	11 ft 0 in (3.4 m)
Maximum Jib Capacity	2000 lbs (900 kg)	2000 lbs (900 kg)	2000 lbs (900 kg)
Upper Boom Articulation	210°	210°	210°
Lower Boom Articulation	101°	101°	101°
Lower Boom Articulation with X	125°	125°	125°

INSULATION GAP:



Upper Boom	9 ft 6 in (2.9 m)	12 ft 0 in (3.7 m)	14 ft 6 in (4.4 m)
Lower Boom	1 ft 0 in (30 cm)	2 ft 0 in (60 cm)	2 ft 0 in (60 cm)

HYDRAULIC SYSTEM:

Operating Pressure	3000 psi (207 bar)
Flow Rate	8 gpm (30 lpm)
Filtration	10 micron pressure 10 micron return 100 mesh suction
System Type	Open Center

OPTIONS:

- Automatic Boom Latch
- Auxiliary Outriggers
- Backup 12-Volt Pump
- Manual Jib Pole Extension
- Hydraulic Jib Pole Extension
- Category D Dielectric Testing and Certification
- Platform Elevator (Single platform only)
- Dual Upper Controls (Dual platforms only)
- Category B Dielectric Testing and Certification
- Various Pedestal Heights
- Lift Eye (2500 lb max)



Note: Specifications on units may vary or change without prior notification due to option selections.

REV. 09/19

VERSALIFT is a leading manufacturer of bucket trucks, digger derricks and cable placers. Customers in the electric utility, telecommunications, forestry and sign, light & traffic industries experience a lower true cost of ownership by choosing Versalift. Our equipment is engineered to be lighter, while keeping the designs simple, which provides advantages like less unscheduled maintenance, greater payloads and ease of maintenance. Versalift has the lowest recall rate in the industry making it the smarter and most reliable choice. Versalift aerial lifts are the only units to feature the patented TruGuard® safety system, which provides additional protection to linemen in the bucket. Versalift is a Time Manufacturing Company, and together with Aspen Aerials has more than 1,000 employees worldwide.

REV. 03/19